

Slide Analysis Information

Estabilidad UD FJC Sede Vivero

Project Summary

File Name: PerfilS1S2TerrAncladoSIN
Slide Modeler Version: 6.005
Project Title: Estabilidad UD FJC Sede Vivero
Author: Ing. Paola Murcia para <SODICO>
Date Created: 5/03/2019, 3:05:39 p. m.

General Settings

Units of Measurement: Metric Units
Time Units: days
Permeability Units: meters/second
Failure Direction: Right to Left
Data Output: Standard
Maximum Material Properties: 20
Maximum Support Properties: 20

Analysis Options

Analysis Methods Used

Bishop simplified
Janbu simplified

Number of slices: 25
Tolerance: 0.005
Maximum number of iterations: 50
Check $m\alpha < 0.2$: Yes
Initial trial value of FS: 1
Steffensen Iteration: Yes

Groundwater Analysis

Groundwater Method: Ru Coefficient
Pore Fluid Unit Weight: 9.81 kN/m³
Advanced Groundwater Method: None

Random Numbers

Pseudo-random Seed: 10116

Random Number Generation Method: Park and Miller v.3

Surface Options

Surface Type: Circular
 Search Method: Slope Search
 Number of Surfaces: 5000
 Upper Angle: Not Defined
 Lower Angle: Not Defined
 Composite Surfaces: Disabled
 Reverse Curvature: Create Tension Crack
 Minimum Elevation: Not Defined
 Minimum Depth: Not Defined

Loading

2 Distributed Loads present



Distributed Load 1

Distribution: Constant
 Magnitude [kN/m²]: 20
 Orientation: Normal to boundary

Distributed Load 2

Distribution: Constant
 Magnitude [kN/m²]: 10
 Orientation: Normal to boundary

Material Properties

Property	Arcilla Dura	Arenisca
Color		
Strength Type	Mohr-Coulomb	Mohr-Coulomb
Unit Weight [kN/m ³]	21	22
Cohesion [kPa]	100	250
Friction Angle [deg]	0	30
Ru Value	0.1	0.1

Support Properties

Support 1

Support Type: Grouted Tieback

Force Application: Active
Out-of-Plane Spacing: 2 m
Tensile Capacity: 148 kN
Plate Capacity: 500 kN
Bond length: 10.000 m
Bond Strength: 31 kN/m

Global Minimums

Method: bishop simplified

FS: 2.159710
Center: 101586.900, 100210.287
Radius: 0.801
Left Slip Surface Endpoint: 101587.108, 100209.514
Right Slip Surface Endpoint: 101587.673, 100210.079
Resisting Moment=67.0547 kN-m
Driving Moment=31.048 kN-m

Method: janbu simplified

FS: 1.151920
Center: 101586.900, 100210.287
Radius: 0.801
Left Slip Surface Endpoint: 101587.108, 100209.514
Right Slip Surface Endpoint: 101587.673, 100210.079
Resisting Horizontal Force=56.5324 kN
Driving Horizontal Force=49.0769 kN

Valid / Invalid Surfaces

Method: bishop simplified

Number of Valid Surfaces: 2517
Number of Invalid Surfaces: 2483

Error Codes:

Error Code -105 reported for 50 surfaces
Error Code -106 reported for 8 surfaces
Error Code -107 reported for 564 surfaces
Error Code -108 reported for 121 surfaces
Error Code -112 reported for 1740 surfaces

Method: janbu simplified

Number of Valid Surfaces: 2076
Number of Invalid Surfaces: 2924

Error Codes:

Error Code -105 reported for 50 surfaces
 Error Code -106 reported for 8 surfaces
 Error Code -107 reported for 564 surfaces
 Error Code -108 reported for 562 surfaces
 Error Code -112 reported for 1740 surfaces

Error Codes

The following errors were encountered during the computation:

- 105 = More than two surface / slope intersections with no valid slip surface.
- 106 = Average slice width is less than 0.0001 * (maximum horizontal extent of soil region). This limitation is imposed to avoid numerical errors which may result from too many slices, or too small a slip region.
- 107 = Total driving moment or total driving force is negative. This will occur if the wrong failure direction is specified, or if high external or anchor loads are applied against the failure direction.
- 108 = Total driving moment or total driving force < 0.1. This is to limit the calculation of extremely high safety factors if the driving force is very small (0.1 is an arbitrary number).
- 112 = The coefficient $M\text{-}\alpha = \cos(\alpha)(1 + \tan(\alpha)\tan(\phi))/F < 0.2$ for the final iteration of the safety factor calculation. This screens out some slip surfaces which may not be valid in the context of the analysis, in particular, deep seated slip surfaces with many high negative base angle slices in the passive zone.

Slice Data

Global Minimum Query (bishop simplified) - Safety Factor: 2.15971

Slice Number	Width [m]	Weight [kN]	Base Material	Base Cohesion [kPa]	Base Friction Angle [degrees]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]
1	0.022613	0.00386524	Arcilla Dura	100	0	46.3025	100	-13.0341	0.017093	-13.0512
2	0.022613	0.0113354	Arcilla Dura	100	0	46.3025	100	-14.1869	0.0501277	-14.237
3	0.022613	0.0185051	Arcilla Dura	100	0	46.3025	100	-15.4013	0.081834	-15.4832
4	0.022613	0.0252943	Arcilla Dura	100	0	46.3025	100	-16.6816	0.111858	-16.7934
5	0.022613	0.031723	Arcilla Dura	100	0	46.3025	100	-18.0339	0.140287	-18.1742
6	0.022613	0.0377111	Arcilla Dura	100	0	46.3025	100	-19.4702	0.166768	-19.6369
7	0.022613	0.0433788	Arcilla Dura	100	0	46.3025	100	-20.9945	0.191832	-21.1863
8	0.022613	0.0485659	Arcilla Dura	100	0	46.3025	100	-22.6252	0.21477	-22.8399
9	0.022613	0.0533524	Arcilla Dura	100	0	46.3025	100	-24.3718	0.235937	-24.6077
10	0.022613	0.0576382	Arcilla Dura	100	0	46.3025	100	-26.2545	0.25489	-26.5094
11	0.022613	0.0614634	Arcilla Dura	100	0	46.3025	100	-28.2905	0.271806	-28.5623

12	0.022613	0.0647478	Arcilla Dura	100	0	46.3025	100	-30.5064	0.28633	-30.7928
13	0.022613	0.0674114	Arcilla Dura	100	0	46.3025	100	-32.9348	0.29811	-33.2329
14	0.022613	0.0695143	Arcilla Dura	100	0	46.3025	100	-35.6093	0.307409	-35.9167
15	0.022613	0.0709162	Arcilla Dura	100	0	46.3025	100	-38.5828	0.313608	-38.8964
16	0.022613	0.0715971	Arcilla Dura	100	0	46.3025	100	-41.918	0.31662	-42.2346
17	0.022613	0.0714769	Arcilla Dura	100	0	46.3025	100	-45.7007	0.316088	-46.0168
18	0.022613	0.0703754	Arcilla Dura	100	0	46.3025	100	-50.0539	0.311217	-50.3651
19	0.022613	0.0681925	Arcilla Dura	100	0	46.3025	100	-55.1464	0.301564	-55.448
20	0.022613	0.0647478	Arcilla Dura	100	0	46.3025	100	-61.2334	0.28633	-61.5197
21	0.022613	0.0597811	Arcilla Dura	100	0	46.3025	100	-68.7181	0.264366	-68.9825
22	0.022613	0.0528917	Arcilla Dura	100	0	46.3025	100	-78.2889	0.2339	-78.5228
23	0.022613	0.043479	Arcilla Dura	100	0	46.3025	100	-91.244	0.192274	-91.4363
24	0.022613	0.0304213	Arcilla Dura	100	0	46.3025	100	-110.462	0.13453	-110.596
25	0.022613	0.0114355	Arcilla Dura	100	0	46.3025	100	2268.96	0.0505706	2268.91

Global Minimum Query (janbu simplified) - Safety Factor: 1.15192

Slice Number	Width [m]	Weight [kN]	Base Material	Base Cohesion [kPa]	Base Friction Angle [degrees]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]
1	0.022613	0.00386524	Arcilla Dura	100	0	86.8116	100	-24.5826	0.017093	-24.5997
2	0.022613	0.0113354	Arcilla Dura	100	0	86.8116	100	-27.0325	0.0501277	-27.0826
3	0.022613	0.0185051	Arcilla Dura	100	0	86.8116	100	-29.5863	0.081834	-29.6681
4	0.022613	0.0252943	Arcilla Dura	100	0	86.8116	100	-32.2487	0.111858	-32.3606
5	0.022613	0.031723	Arcilla Dura	100	0	86.8116	100	-35.0323	0.140287	-35.1726
6	0.022613	0.0377111	Arcilla Dura	100	0	86.8116	100	-37.9562	0.166768	-38.123
7	0.022613	0.0433788	Arcilla Dura	100	0	86.8116	100	-41.033	0.191832	-41.2248
8	0.022613	0.0485659	Arcilla Dura	100	0	86.8116	100	-44.2903	0.21477	-44.5051

9	0.022613	0.0533524	Arcilla Dura	100	0	86.8116	100	-47.7495	0.235937	-47.9855
10	0.022613	0.0576382	Arcilla Dura	100	0	86.8116	100	-51.4445	0.25489	-51.6994
11	0.022613	0.0614634	Arcilla Dura	100	0	86.8116	100	-55.409	0.271806	-55.6808
12	0.022613	0.0647478	Arcilla Dura	100	0	86.8116	100	-59.6898	0.28633	-59.9762
13	0.022613	0.0674114	Arcilla Dura	100	0	86.8116	100	-64.345	0.29811	-64.6431
14	0.022613	0.0695143	Arcilla Dura	100	0	86.8116	100	-69.44	0.307409	-69.7474
15	0.022613	0.0709162	Arcilla Dura	100	0	86.8116	100	-75.0682	0.313608	-75.3818
16	0.022613	0.0715971	Arcilla Dura	100	0	86.8116	100	-81.3465	0.31662	-81.6631
17	0.022613	0.0714769	Arcilla Dura	100	0	86.8116	100	-88.4329	0.316088	-88.7489
18	0.022613	0.0703754	Arcilla Dura	100	0	86.8116	100	-96.5503	0.311217	-96.8615
19	0.022613	0.0681925	Arcilla Dura	100	0	86.8116	100	-106.012	0.301564	-106.314
20	0.022613	0.0647478	Arcilla Dura	100	0	86.8116	100	-117.289	0.28633	-117.575
21	0.022613	0.0597811	Arcilla Dura	100	0	86.8116	100	-131.128	0.264366	-131.392
22	0.022613	0.0528917	Arcilla Dura	100	0	86.8116	100	-148.802	0.2339	-149.036
23	0.022613	0.043479	Arcilla Dura	100	0	86.8116	100	-172.723	0.192274	-172.915
24	0.022613	0.0304213	Arcilla Dura	100	0	86.8116	100	-208.242	0.13453	-208.377
25	0.022613	0.0114355	Arcilla Dura	100	0	86.8116	100	2142.32	0.0505706	2142.27

List Of Coordinates

Line Load

X	Y
101606	100214
101598	100214

Line Load

X	Y
101578	100207
101577	100207

101570	100207
--------	--------

External Boundary

X	Y
101569	100188
101611	100188
101611	100211
101611	100214
101598	100214
101597	100214
101597	100214
101597	100214
101597	100214
101596	100214
101595	100214
101595	100214
101595	100214
101593	100214
101592	100213
101591	100213
101591	100212
101591	100211
101589	100211
101588	100210
101587	100210
101587	100209
101585	100209
101584	100208
101583	100208
101583	100207
101577	100207
101569	100207
101569	100202

Material Boundary

X	Y
101569	100202
101570	100202
101571	100202
101571	100202
101572	100202
101573	100202
101574	100202

101575	100202
101575	100202
101576	100203
101576	100203
101577	100203
101577	100203
101577	100203
101578	100203
101578	100204
101579	100204
101579	100204
101579	100204
101579	100204
101580	100204
101580	100204
101581	100204
101581	100204
101581	100204
101582	100204
101582	100204
101582	100205
101583	100205
101584	100205
101585	100205
101585	100205
101586	100206
101586	100206
101586	100206
101587	100206
101587	100206
101587	100206
101588	100206
101589	100206
101589	100206
101589	100207
101590	100207
101590	100207
101591	100207
101591	100207
101591	100207
101592	100208
101592	100208
101593	100208
101593	100208
101593	100208

101594	100208
101594	100208
101594	100208
101595	100208
101595	100208
101595	100208
101596	100209
101596	100209
101596	100209
101597	100209
101598	100209
101599	100209
101599	100209
101600	100210
101600	100210
101600	100210
101601	100210
101601	100210
101601	100210
101602	100210
101602	100210
101603	100210
101603	100210
101604	100210
101604	100210
101605	100210
101606	100210
101608	100211
101611	100211